

NO-HEAT™ SHRINKABLE TUBING

NO-HEAT Shrink Tubing product requires no heat source to shrink over your connectors, wires, or cable sheaths. The tubing coverage is made possible by a spiral cut, removable support core that keeps the tubing in its expanded state. As the core is unraveled, the EPDM (Ethylene Propylene Rubber) tube conforms to the substrate and forms a water-resistant seal. In addition to being water-resistant, **NO-HEAT** Shrink Tubing resists fungus, acids and alkalis.

Operating Temperature Range: 0°F (-18°C) to 240°F (115°C)

Shrink Ratio: See table below

Shrink Temperature: N/A

Standard Colors: Black

Standard Shipping Length: See table below

Catalog Number Size	Cable Diameter Range (Minimum - Maximum)		Recovered Wall Thickness		Relaxed Tube Length	
	inches	mm	inches	mm	inches	mm
NST-#2 X 6"	0.310 - 0.560	7.80 - 14.30	0.060	1.52	6.00	152
NST-#3 X 8"	0.400 - 0.820	10.10 - 20.90	0.066	1.68	8.00	203
NST-#4 X 9"	0.550 - 1.180	13.90 - 30.10	0.064	1.62	9.00	229
NST-#4 X 11"	0.550 - 1.180	13.90 - 30.10	0.064	1.62	11.00	279
NST-#5 X 6"	0.690 - 1.380	17.50 - 35.10	0.073	1.85	6.00	152
NST-#5 X 12"	0.690 - 1.380	17.50 - 35.10	0.073	1.85	12.00	305
NST-#5 X 16"	0.690 - 1.380	17.50 - 35.10	0.073	1.85	16.00	406
NST-#6 X 6"	0.930 - 1.940	23.60 - 49.30	0.070	1.78	6.00	152
NST-#6 X 12"	0.930 - 1.940	23.60 - 49.30	0.070	1.78	12.00	305
NST-#6 X 18"	0.930 - 1.940	23.60 - 49.30	0.070	1.78	18.00	457
NST-#7 X 6"	1.270 - 2.670	32.20 - 67.80	0.067	1.70	6.00	152
NST-#7 X 9"	1.270 - 2.670	32.20 - 67.80	0.067	1.70	9.00	229
NST-#7 X 12"	1.270 - 2.670	32.20 - 67.80	0.067	1.70	12.00	305
NST-#7 X 18"	1.270 - 2.670	32.20 - 67.80	0.067	1.70	18.00	457
NST-#8 X 9"	1.680 - 3.690	42.60 - 93.70	0.061	1.55	9.00	229
NST-#8 X 18"	1.680 - 3.690	42.60 - 93.70	0.061	1.55	18.00	457

