

SLV-130 combines fiberglass and a vinyl insulation jacket. It has good abrasion resistance, excellent cut through characteristics, and non-fray ends. It is widely used in applications up to 265°F (130°C) where tubing is subject to knotting, bending, and high torque.

SLV-1200 is a sleeving of tightly braided 100% fiberglass for use in temperatures up to 1200°F (650°C). Closely woven construction provides maximum abrasion resistance and high flexibility. The material is treated to remove all organic matter and to render the glass braid fray-resistant.

Applicable Specifications: MIL-I-3190, Class B, Grade B
 Operating Temp. Range: -5°F (-20°C) to 265°F (130°C)
 Standard Color: Black*
 Std. Shipping Length: Spools

Applicable Specifications: MIL-I-3190, Class C
 Operating Temp. Range: -75°F (-60°C) to 1200°F (650°C)
 Standard Color: Natural
 Std. Shipping Length: Spools

**SLV-130 FIBERGLASS W/
VINYL JACKET**

Catalog Number Size	Nominal I.D.		Nominal Wall Thickness		Std. Length ft / spool
	inches	mm	inches	mm	
SLV-130-24	0.022	0.56	0.014	0.36	100, 500
SLV-130-22	0.027	0.69	0.014	0.36	100, 500
SLV-130-20	0.034	0.86	0.014	0.36	100, 500
SLV-130-19	0.038	0.97	0.014	0.36	100, 500
SLV-130-18	0.042	1.07	0.016	0.41	100, 500
SLV-130-17	0.047	1.19	0.016	0.41	100, 500
SLV-130-16	0.053	1.35	0.016	0.41	100, 500
SLV-130-15	0.059	1.50	0.016	0.41	100, 500
SLV-130-14	0.066	1.68	0.018	0.46	100, 500
SLV-130-13	0.076	1.93	0.018	0.46	100, 250
SLV-130-12	0.085	2.16	0.018	0.46	100, 250
SLV-130-11	0.095	2.41	0.018	0.46	100, 250
SLV-130-10	0.106	2.69	0.020	0.50	100, 250
SLV-130-9	0.118	3.00	0.020	0.50	100, 250
SLV-130-8	0.133	3.38	0.020	0.50	100, 250
SLV-130-7	0.148	3.76	0.020	0.50	100, 250
SLV-130-6	0.166	4.22	0.020	0.50	100, 250
SLV-130-5	0.186	4.72	0.020	0.50	100, 250
SLV-130-4	0.208	5.28	0.022	0.55	100, 250
SLV-130-3	0.234	5.94	0.022	0.55	100, 250
SLV-130-#2	0.263	6.68	0.026	0.65	100, 250
SLV-130-#1	0.294	7.47	0.032	0.81	100
SLV-130-0	0.330	8.38	0.032	0.81	100
SLV-130-3/8	0.387	9.83	0.037	0.93	100
SLV-130-7/16	0.450	11.43	0.037	0.93	100
SLV-130-1/2	0.512	13.00	0.037	0.93	100
SLV-130-5/8	0.640	16.26	0.041	1.03	100
SLV-130-3/4	0.768	19.51	0.051	1.28	100
SLV-130-7/8	0.893	22.68	0.057	1.44	100
SLV-130-1"	1.018	25.86	0.057	1.44	100

SLV-1200 FIBERGLASS

Catalog Number Size	Nominal I.D.		Nominal Wall Thickness		Std. Length ft / spool
	inches	mm	inches	mm	
SLV-1200-24	0.022	0.56	0.010	0.25	100, 500
SLV-1200-22	0.027	0.69	0.010	0.25	100, 500
SLV-1200-20	0.034	0.86	0.010	0.25	100, 500
SLV-1200-19	0.038	0.97	0.015	0.38	100, 500
SLV-1200-18	0.042	1.07	0.015	0.38	100, 500
SLV-1200-17	0.047	1.19	0.015	0.38	100, 500
SLV-1200-16	0.053	1.35	0.015	0.38	100, 500
SLV-1200-15	0.059	1.50	0.015	0.38	100, 500
SLV-1200-14	0.066	1.68	0.015	0.38	100, 500
SLV-1200-13	0.076	1.93	0.015	0.38	100, 250
SLV-1200-12	0.085	2.16	0.015	0.38	100, 250
SLV-1200-11	0.095	2.41	0.015	0.38	100, 250
SLV-1200-10	0.106	2.69	0.015	0.38	100, 250
SLV-1200-9	0.118	3.00	0.015	0.38	100, 250
SLV-1200-8	0.133	3.38	0.015	0.38	100, 250
SLV-1200-7	0.148	3.76	0.015	0.38	100, 250
SLV-1200-6	0.166	4.22	0.015	0.38	100, 250
SLV-1200-5	0.186	4.72	0.015	0.38	100, 250
SLV-1200-4	0.208	5.28	0.015	0.38	100, 250
SLV-1200-3	0.234	5.94	0.015	0.38	100, 250
SLV-1200-#2	0.263	6.68	0.020	0.51	100, 250
SLV-1200-#1	0.294	7.47	0.020	0.51	100
SLV-1200-0	0.330	8.38	0.020	0.51	100
SLV-1200-3/8	0.387	9.83	0.032	0.81	100
SLV-1200-7/16	0.450	11.43	0.032	0.81	100
SLV-1200-1/2	0.512	13.00	0.032	0.81	100
SLV-1200-5/8	0.640	16.26	0.032	0.81	100
SLV-1200-3/4	0.768	19.51	0.032	0.81	100
SLV-1200-7/8	0.893	22.68	0.032	0.81	100
SLV-1200-1"	1.018	25.86	0.032	0.81	100

*Additional sizes/colors available, consult factory.