

**SLW-PVCP** is a general-purpose sleeving repair product that employs a light-weight, flexible jacket of vinyl-coated polyester and an adhesive closure. **SLW-PVCP** is valuable in applications where flexibility, tear resistance, and abrasion resistance is required. Installation is as easy as wrapping the product around the wire or cable, removing the protective liner from the adhesive and overlapping the side edges to create a tube.

Operating Temperature Range: -4°F (-20°C) to 212°F (100°C)  
 Flammability: VW-1  
 Standard Color: Black  
 Standard Shipping Length: Spools

Catalog Number Size	Maximum Cable Diameter		Nominal Wall Thickness		Std. Length ft / spool
	inches	mm	inches	mm	
SLW-PVCP-3/4"	0.75	19.1	0.010	0.25	100
SLW-PVCP-1"	1.00	25.4	0.010	0.25	100
SLW-PVCP-1-1/4"	1.25	31.8	0.010	0.25	100
SLW-PVCP-1-1/2"	1.50	38.1	0.010	0.25	100
SLW-PVCP-1-3/4"	1.75	44.5	0.010	0.25	100
SLW-PVCP-2"	2.00	50.8	0.010	0.25	100
SLW-PVCP-2-1/4"	2.25	57.2	0.010	0.25	100
SLW-PVCP-2-1/2"	2.50	63.5	0.010	0.25	100
SLW-PVCP-2-3/4"	2.75	69.9	0.010	0.25	100
SLW-PVCP-3"	3.00	76.2	0.010	0.25	100
SLW-PVCP-3-1/4"	3.25	82.6	0.010	0.25	100
SLW-PVCP-3-1/2"	3.50	88.9	0.010	0.25	100
SLW-PVCP-4"	4.00	101.6	0.010	0.25	100

**SLW-ALPU** is an EMI shielding material that utilizes polyurethane jacketed aluminum foil. This product is ideal for electrical applications where shielding is necessary. **SLW-ALPU** is installed by wrapping the split tubing around the wire or cable assembly and sticking the side edges together using the adhesive liner to form a protective tube.

Avg. Shielding Attenuation: 102 dB (10MHz - 20GHz)  
 Flammability: VW-1  
 Standard Color: Black  
 Standard Shipping Length: Spools

Catalog Number Size	Maximum Cable Diameter		Nominal Wall Thickness		Std. Length ft / spool
	inches	mm	inches	mm	
SLW-ALPU-3/4"	0.75	19.1	0.010	0.25	25, 100
SLW-ALPU-1"	1.00	25.4	0.010	0.25	25, 100
SLW-ALPU-1-1/4"	1.25	31.8	0.010	0.25	25, 100
SLW-ALPU-1-1/2"	1.50	38.1	0.010	0.25	25, 100
SLW-ALPU-1-3/4"	1.75	44.5	0.010	0.25	25, 100
SLW-ALPU-2"	2.00	50.8	0.010	0.25	25, 100
SLW-ALPU-2-1/4"	2.25	57.2	0.010	0.25	25, 100
SLW-ALPU-2-1/2"	2.50	63.5	0.010	0.25	25, 100
SLW-ALPU-2-3/4"	2.75	69.9	0.010	0.25	25, 100
SLW-ALPU-3"	3.00	76.2	0.010	0.25	25, 100
SLW-ALPU-3-1/4"	3.25	82.6	0.010	0.25	25, 100
SLW-ALPU-3-1/2"	3.50	88.9	0.010	0.25	25, 100
SLW-ALPU-3-3/4"	3.75	95.3	0.010	0.25	25, 100
SLW-ALPU-4"	4.00	101.6	0.010	0.25	25, 100