

ProFIT® PRODUCT COMPARISON GUIDE

WALL TYPE	JACKET MATERIAL	PRODUCT	WALL STYLE			INNER WALL		FLEXIBILITY			CROSS-LINKED	OPERATING TEMPERATURE (°F)	OPERATING TEMPERATURE (°C)	
			THIN-WALL	MEDIUM-WALL	HEAVY-WALL	ADHESIVE-LINED	MELTABLE	VERY FLEXIBLE	FLEXIBLE	SEMI-RIGID				
SINGLE WALL	POLYOLEFIN	HIX	X					X		X		-67 to 275	-55 to 135	
		HIX-VW1	X					X		X		-67 to 275	-55 to 135	
		HIX3X	X						X		X		-67 to 275	-55 to 135
		H4X	X						X		X		-67 to 275	-55 to 135
		HIX-G/Y	X						X		X		-67 to 275	-55 to 135
		HRX	X							X	X		-67 to 275	-55 to 135
		HLT	X						X		X		-67 to 275	-55 to 135
		HLT3X	X						X		X		-67 to 275	-55 to 135
	FLUOROPOLYMER	HKX	X							X	X		-67 to 347	-55 to 175
		HKFX	X							X	X		-67 to 302	-55 to 150
		HVFX	X						X		X		-67 to 302	-55 to 150
		HTX	X							X			-103 to 500	-75 to 260
		HSX		X							X		-103 to 500	-75 to 260
		HFX	X								X		-103 to 500	-75 to 260
		HFEP1.3	X							X			-103 to 392	-75 to 200
		HFEP1.6	X							X			-103 to 392	-75 to 200
	PVC	HVX	X							X			-04 to 221	-20 to 105
		HCX	X							X	X		-04 to 221	-20 to 105
		HLF	X								X		-04 to 212	-20 to 100
	ELASTOMER	HNTFR		X						X	X		-94 to 250	-70 to 121
		HVT		X						X	X		-40 to 392	-40 to 200
DUAL WALL	POLYOLEFIN	HAT	X			X			X		X		-67 to 230	-55 to 110
		HWP		X		X			X		X		-40 to 230	-40 to 110
		HCATV			X	X				X	X		-67 to 257	-55 to 125
		HW3X			X	X				X	X		-67 to 194	-55 to 90
		HW3XFR			X	X				X	X		-67 to 194	-55 to 90
		HML		X		X				X	X		-67 to 230	-55 to 110
		HML4X		X		X				X	X		-67 to 230	-55 to 110
		HES1000		X		X				X	X		-40 to 266	-40 to 130
		HES2000		X		X				X	X		-40 to 266	-40 to 130
		HIM			X		X			X	X		-67 to 230	-55 to 110
	FLUOROPOLYMER	HTIM			X		X			X		-100 to 450	-73 to 232	
SPECIALTY PRODUCTS	HSF	X						X				-40 to 257	-40 to 125	
	HSF3X	X						X				-40 to 257	-40 to 125	
	NST			X					X			0 to 240	-18 to 115	
	HSMG-A	X							X	X		-67 to 347	-55 to 175	
	HSMG-C	X							X	X		-67 to 302	-55 to 150	
	HSMG-E	X							X	X		-94 to 221	-70 to 105	
	HSLD	X							X	X		-67 to 275	-55 to 135	
	HSRT	X						X		X		-67 to 275	-55 to 135	

ProFIT® PRODUCT COMPARISON GUIDE

PRODUCT	SHRINK TEMP (°F)		SHRINK RATIO	SUPPLIED I.D. SIZE RANGE (inches)		SUPPLIED I.D. SIZE RANGE (mm)		COLORS AVAILABLE	CLEAR AVAILABLE	FLAME-RETARDANT	UL RECOGNIZED	UL VW-1 RATED	SAE-AMS-DTL-23053	SEE CATALOG PAGE
HIX	250	121	2:1	0.046 to 5.000	1.17 to 127.00	X	X	*	*	*	/5	5		
HIX-VW1	176	80	2:1	0.046 to 2.000	1.17 to 50.80	X		X	X	X	/5	6		
HIX3X	248	120	3:1	0.118 to 1.535	3.00 to 39.00	X		X	X			6		
H4X	250	121	4:1	0.750 to 4.500	19.05 to 114.30	X		X			/5	7		
HIX-G/Y	250	121	2:1	0.125 to 1.000	3.18 to 25.40	X		X	X			20		
HRX	275	135	2:1	0.046 to 0.500	1.17 to 12.70	X	X	*	*		/6	7		
HLT	176	80	2:1	0.046 to 1.000	1.17 to 25.40	X		X	X	X	/5	8		
HLT3X	176	80	3:1	0.093 to 1.000	2.36 to 25.40	X		X	X	X		8		
HKX	347	175	2:1	0.046 to 1.500	1.17 to 38.10	X	X	X	X	X	/8	14		
HKFX	302	150	2:1	0.046 to 1.000	1.17 to 25.40		X	X	X	X	/18	14		
HVFX	302	150	2:1	0.046 to 1.000	1.17 to 25.40	X		X	X	X	/18	11		
HTX	662	350	1.5:1	0.034 to 0.470	0.86 to 11.94	X	X	X			/12	12		
HSX	662	350	1.5:1	0.050 to 0.470	1.27 to 11.94	X	X	X			/12	12		
HFX	662	350	4:1	0.078 to 1.250	1.98 to 31.75		X	X			/12	12		
HFEP1.3	430	221	1.3:1	0.031 to 1.330	0.79 to 33.78	X	X	X			/11	13		
HFEP1.6	430	221	1.6:1	0.093 to 2.000	2.36 to 50.80	X	X	X			/11	13		
HVX	212	100	2:1	0.063 to 2.000	1.60 to 50.80	X	X	X	X	X	/2	16		
HCX	212	100	2:1	0.046 to 2.000	1.19 to 50.80	X		X	X	X	/2	16		
HLF	275	135	2:1	0.748 to 6.339	19.00 to 161.00	X	X	X				15		
HNTFR	275	135	1.75:1	0.125 to 3.000	3.18 to 76.20	X		X	X		/1	17		
HVT	347	175	2:1	0.125 to 2.000	3.18 to 50.80	X		X			/13	17		
HAT	250	121	2:1	0.125 to 1.500	3.18 to 38.10	X		*	*		/4	9		
HWP	257	125	3:1	0.125 to 1.500	3.18 to 38.10	X		X	X			10		
HCATV	248	120	3:1	0.374 to 2.756	10.00 to 70.00	X		X				22		
HW3X	250	121	3:1	0.400 to 4.000	10.16 to 101.60	X		X				24		
HW3XFR	250	121	3:1	0.400 to 4.000	10.16 to 101.60	X		X			/15	24		
HML	230	110	3:1	0.118 to 1.575	3.00 to 40.00	X		X			/4	9		
HML4X	230	110	4:1	0.157 to 2.047	4.00 to 52.00	X		X			/4	9		
HES1000	275	135	4:1	0.225 to 0.700	5.72 to 17.78		X		X			10		
HES2000	275	135	4:1	0.225 to 0.700	5.72 to 17.78	X		X	X			10		
HIM	275	135	V	0.125 to 1.500	3.18 to 38.10	X		X	X		/4	11		
HTIM	680	360	V	0.036 to 0.950	0.91 to 24.13	X	X	X				15		
HSF	275	135	2:1	0.472 to 2.760	12.00 to 70.00	X		X				20		
HSF3X	275	135	3:1	0.709 to 2.362	18.00 to 60.00	X		X				20		
NST	N/A	N/A	V	V	V	X						23		
HSMG-A	347	175	2:1	0.063 to 0.500	1.60 to 25.40	X	X	X			/8	18		
HSMG-C	302	150	2:1	0.063 to 0.500	1.60 to 25.40	X		X			/18	18		
HSMG-E	230	110	2:1	0.063 to 0.500	1.60 to 25.40	X	X	*				19		
HSLD	176	80	2:1	0.187 to 1.000	4.75 to 25.40	X		X				24		
HSRT	176	80	V	V	V	X		X				21		

* Clear not included.

V = Application specific, review catalog page for more information.