

SLV-155 is used in motor lead-outs, crossovers, transformers, and coils. It is also utilized for protective and thermal insulation in ovens, furnases, ovens, lighting, and other consumer and industrial appliances. This is sutiable for applications up to 311°F (155°C).

Applicable Specifications: MIL-I-3190/3
 Operating Temperature Range: -13°F (-25°C) to 311°F (155°C)
 Standard Colors: Natural*
 Standard Shipping Length: Spools or lengths, depending on size

SLV-155 ACR. COATED FIBERGLASS

Catalog Number Size	Nominal I.D.		Nominal Wall Thickness	
	inches	mm	inches	mm
SLV-155-24	0.022	0.56	0.024	0.61
SLV-155-22	0.027	0.69	0.024	0.61
SLV-155-20	0.034	0.86	0.024	0.61
SLV-155-19	0.038	0.97	0.024	0.61
SLV-155-18	0.042	1.07	0.024	0.61
SLV-155-17	0.047	1.19	0.024	0.61
SLV-155-16	0.053	1.35	0.024	0.61
SLV-155-15	0.059	1.50	0.029	0.74
SLV-155-14	0.066	1.68	0.029	0.74
SLV-155-13	0.076	1.93	0.029	0.74
SLV-155-12	0.085	2.16	0.029	0.74
SLV-155-11	0.095	2.41	0.029	0.74
SLV-155-10	0.106	2.69	0.029	0.74
SLV-155-9	0.118	3.00	0.029	0.74
SLV-155-1/8	0.125	3.18	0.029	0.74
SLV-155-8	0.133	3.38	0.029	0.74
SLV-155-7	0.148	3.76	0.029	0.74
SLV-155-6	0.166	4.22	0.029	0.74
SLV-155-5	0.186	4.72	0.029	0.74
SLV-155-4	0.208	5.28	0.029	0.74
SLV-155-3	0.234	5.94	0.042	1.07
SLV-155-1/4	0.250	6.35	0.042	1.07
SLV-155-#2	0.263	6.68	0.042	1.07
SLV-155-#1	0.294	7.47	0.042	1.07
SLV-155-5/16	0.312	7.92	0.042	1.07
SLV-155-0	0.330	8.38	0.042	1.07
SLV-155-3/8	0.375	9.53	0.045	1.14
SLV-155-7/16	0.438	11.13	0.045	1.14
SLV-155-1/2	0.500	12.70	0.045	1.14
SLV-155-9/16	0.562	14.27	0.045	1.14
SLV-155-5/8	0.625	15.88	0.045	1.14
SLV-155-3/4	0.750	19.05	n/a	n/a
SLV-155-7/8	0.875	22.23	n/a	n/a
SLV-155-1"	1.000	25.40	n/a	n/a

*Additional sizes/colors available, consult factory.